



## Wireless receiver / repeater RF RxT SW915-USB Material number: 1278205

### Features/Options:

- Different operating modes
- USB-Standard Receiver Mode
- USB Gateway Mode
- Sniffer Mode
- Repeater (1-Level and 2-Level Repeater Mode)
- Virtual COM Port driver for Microsoft Windows, Linux, Apple Mac

### Product image



### Technical data

Standards	EN 60947-5-1; EN 61000-6-2, -6-3, EN 61000-4-2, -4-20, -4-4, -4-6; EN 301 489-1; EN 301 489-3; EN 300 220-1; EN 300 220-2
Connection	USB 2.0
Degree of protection	IP 30 to IEC/EN 60529
Receiver mode	40 sWave transmitters
Gateway mode	indefinite number of transmitters
Power supply	via USB interface
Rated operating current $I_e$	< 60 mA
Rated operating voltage $U_e$	5 VDC (USB interface)
Frequency	915 MHz (USA, Canada and Mexico)
Display	green LED: operating state, orange LED: switching conditions
Operation cycles	approx. 12000 telegrams at repetitions/h
Ambient temperature	0 °C ... +55 °C
Dimensions	70 x 23 x 9 mm (incl. transportation cap)
Note	no external antenna required
Approvals	USA: FCC: XK5-RFRXSW915; Canada: IC: 5158A-RFRXSW915; Mexico: IFT/223/UCS/DG-AUSE/6773/2017