

# SPECIFICATION CONTROL DRAWING


**55PC212A**

TITLE TWO CONDUCTOR CABLE, FLAT BRAID SHIELDED, JACKETED, 600 VOLT

Date 3-15-95

Revision

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.



CONSTRUCTION DETAILS									
PART NUMBER	CONDUCTOR SIZE (AWG)	SHIELD STRAND THICKNESS (± .0004)	JACKET THICKNESS (in.)		DIAMETER (in.)			WEIGHT (lbs/1000 ft.)	
			LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC212A-26-	26	.0015	.0060	.0075	.080	.085	.090	5.28	5.71

### CABLE RATINGS AND ADDITIONAL REQUIREMENTS

**TEMPERATURE RATING: 150°C**  
 Maximum continuous conductor temperature  
**VOLTAGE RATING: 600 volts (rms)**  
**DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz**  
**CROSSLINKING PROOF TEST: 300 ± 3°C for 1 hour**  
**JACKET COLOR: White preferred**  
**JACKET ELONGATION AND TENSILE STRENGTH:**  
 Elongation, 50% (minimum)  
 Tensile Strength, 5000 lbf/in<sup>2</sup> (minimum)  
**JACKET FLAWS:**  
 Spark Test, 1000 volts (rms), 60 Hz, 100% test  
 Impulse Dielectric Test, 6.0 kV (peak), 100% test

**SHIELD COVERAGE: 85% (minimum)**  
**VOLTAGE WITHSTAND TEST (POST ENVIRONMENTAL):**  
 1000 volts (rms), 60 Hz, 1 minute

**PART NUMBER:**  
 The "" in the part numbers above shall be replaced by a color code designators with a dash separating the component wire color from the jacket color.  
 Example: AWG 26, red and blue component wires; white jacket: 55PC212A-26-2/6-9

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.