



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: DC 30V, 0.3A
 5. CONTACT MATERIAL:
PHOSPHOR BRONZE W/ SILVER PLATING
 6. CONTACT RESISTANCE: 20 mili-Ohms max.
 7. DIELECTRIC STRENGTH: 1,000V rms@ Sea Level
 8. OPERATING FORCE: 230±100gf
 9. TRAVEL : FULL 3.5mm; LOCK 2.5mm

CIRCUIT: SPDT
CONTACT CONFIGURATION

<ACTUATOR DETAIL> SCALE 4:1

REV.		ECN No.		DESCRIPTION		DATE		CHKD	
A		12943		RELEASED FOR PRODUCTION		3/21/03		AR	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED									
TITLE		SCALE		DATE		DR		DWG	
LC1258EENS		2:1		3/21/03		AR		P070225	
E-SWITCH®								REV	
								A	