E D D D D D D D D D D D D D D D D D D D										
R 22.6 Max 4 1 1 1 1 1 1 1 1 1 1 1 1 1										
Keying Shown as example										
CHARACTERISTICS Connector dimension										
Dim Nominal -Standard : Based on NIL-DTL-38999 Series III A 38.1±0.3 -Shell Material : Aluminium B 23.82±0.1/-0.15 -Shell Plating : Olive drab Cadmium R 32.5Max -Insulator : Thermoplastic S 34.9±0.4 -Contacts : Copper Alloy VV THREAD M18x1-6g										
-Seals & Grommet : Silicon Elastomer Country Jurisdiction & Control List FR Not Listed	2									
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories										
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours										
	DD N°									
TITLE Aluminium Receptacle 8D series										
BASIC SERIES: 8D 7 - 13 W 26 A N SUEL TYPE - Low - L Double										
A SHELL TYPE : Jam nut Receptacie CONTACT TYPE : Standard Crimp Contact	1									
SHELL SIZE : 13 CONTACT TYPE : PIN(500 Matings)	ı									
	IEET ./2									
H G F E D C B A										

	T	G		П		Г	Π		D	0		σ	Þ	>	_
4			Panel cutout JAM NUT RECEPTACLE (TYPE 7)										4		
ω.	Ctc A B C D E F 1 2	6#22D 13-26 X 0 2.47 2.47 0 -2.47 -2.47 3.25 -3.25	Y 3.47 4.34 -4.34 -3.47 -4.34 4.34 0 0							B 24.26	minal +0/-0.25 +0.25/-0				3
N										the Specifications issu (professional PN: 16 First Release	ne Products which do led by either of the P recommendation, te Country FR 8D713W26	bes not comply wi arties or by a thir echnical notice.) Jurisdiction & Not Li	th d party Control List	MOD N°	2
	H								ISS DATE Designed By: TITLE SCALE NA SOURIAU	U www.so	Aluminium Red General linear Tolerances: ± DURIAU.COM OURIAU DR BD713W26A	Ceptacle 8D	DMER DRAWING SERIES RDS / PROJECT 859 is document is the p SOURIAU it must not be repro- nmunicated without	property of duced or	1