

Technical specification:

Rated voltage: 3pos 4pos
IEC 61076-2-104 60 V 30 V

Current rating: 3 A bei 40°C
IEC 61076-2-104

Insulation resistance: >=100 MΩ
IEC 60512

Pollution degree: 3/2
IEC 60664-1



Degree of protection: IP 67, in mated condition
IEC 60529

Temperature range: -30°C ... +85°C
IEC 60664-1

Mating cycles: >=100
IEC 60512-9a

Materials:

Contact: CuZn
Contact plating: Nickel, gold plated
Contact carrier: PA GF, UL 94



| Part no: | Description: | Pos |
|----------|--------------------|-----|
| 42-01004 | SAL - 8 - ESP3 - L | 3 |
| 42-01006 | SAL - 8 - ESP4 - L | 4 |

DO NOT ALTER CAD DRAWING BY HAND
Directive 2002/95/EC RoHS compliant

Index: c 02.03.11 fro Ä3914
Data sheet revised

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH

| | date | name |
|-------|----------|---------|
| drawn | 15.10.08 | Fromm |
| appd. | 15.10.08 | Mankopf |



title:
Male socket M8x1 with soldering version

dwg no:
42K1A096

part no: