SHEET OF



PARTS LIST			
ITEM	QTY.	PART NO.	PART DESCRIPTION
1	1	F040040	D16 EE T1 4
2	1	F050405	50-004-05 (INCANDESCENT)
3	1	F050204	50-002-04 (TRANSPARENT RED lens)

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4
   X.XX=±0.25
3. RATINGS: 5A@250V AC,
   8A@125V AC
4. LAMP VOLTAGE: 28V AC/DC @40mA (Incandescent)
5. CONTACT MATERIAL: COPPER ALLOY W/Gold Plating
6. TRAVEL: 3.0mm (Total)
7. MECHANICAL LIFE: >100,000 Cycles
8. ELECTRICAL LIFE: >50,000 Cycles
9. INSULATION RESISTANCE: >1000 mILLI-OHMS
10. OPERATING TEMP: -20°C to 55°C



CIRCUIT: 4PST

CONTACT CONFIGURATION



RECOMMENDED PANEL MOUNTING

SCALE 1:1

REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	12431	RELEASE FOR PRODUCTION	9/19/02	CJB

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

TITLE: D16 EE T14 C RED TRANSPARENT/CONCAVE LENS

SCALE	DATE	DR	DWG	REV
1.5:1	9/19/02	CB	XF0505P	A