

**Part Number: 9L28050**



**Flat Gray Ribbon Cable 9L280 Series, #28-50c, .050" Pitch**

**Product Description**

Belden .050" pitch gray ribbon cable was designed for general purpose electronic interconnect applications. The cable provides reliable mass-termination to standard IDC connectors.

**Technical Specifications**

**Physical Characteristics (Overall)**

**Conductor**

AWG	Material	Construction n x D	No. of Conductors
28	TC - Tinned Copper	Stranded	50

Conductor Count:	50
Conductor Size:	28 AWG

**Insulation**

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.01 in

**Color Chart**

Number	Color
	Gray
3	

**Outer Shield Material**

Material
Unshielded

**Outer Jacket Material**

Nominal Wall Thickness
0.035 in

**Construction and Dimensions**

Cond Spacing Center-Center:	.050 in
-----------------------------	---------

**Cabling**

Twists
3 twist/ft

OuterJacket1, Nominal Width:	2.50 in
Print Legend:	BELDEN-T 28 AWG CSA AWM I A 105°C 300 V FT1 LL7874 (UL LOGO) AWM STYLE 2651 VW-1 E12683

**Electrical Characteristics**

**Conductor DCR**

Max. DCR Unbalance	Nominal Conductor DCR
3 %	68.2 Ohm/1000ft

**Capacitance**

Element	Nom. Capacitance Conductor to Conductor
@ 1 kHz (GSG)	18 pF/ft

@ 1 MHz (GS)	10 pF/ft
@ 1 MHz (GSG)	15 pF/ft

Shielding:	Unshielded
------------	------------

#### Inductance

Element	Nominal Inductance
@ 1 MHz (GS)	0.29 $\mu$ H/ft
@ 1 MHz (GSG)	0.2 $\mu$ H/ft

#### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Impedance Description
150 Ohm	(GS)
105 Ohm	(GSG)

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
10 MHz	2.8 dB/100ft
20 MHz	4.8 dB/100ft
30 MHz	6.5 dB/100ft
40 MHz	8.3 dB/100ft
50 MHz	9.8 dB/100ft
60 MHz	12 dB/100ft
70 MHz	13 dB/100ft
80 MHz	14 dB/100ft
90 MHz	15.8 dB/100ft
100 MHz	17 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.4 ns/ft	72 %

#### Unbalanced Crosstalk

Element	Typical Unbalanced NEXT %	Typical Unbalanced FEXT %	Typical Cross Talk Pulse Rise Time (ns)
10 ft. sample length	4.8 MHz	7 MHz	3 ns
10 ft. sample length	3.5 MHz	4.7 MHz	5 ns
10 ft. sample length	3 MHz	3 MHz	7 ns

#### High Freq

Frequency [MHz]
10 MHz
20 MHz
30 MHz
40 MHz
50 MHz
60 MHz
70 MHz
80 MHz
90 MHz
100 MHz

#### Current

Max. Recommended Current [A]
per conductor @ 20°C : 1 A

#### Voltage

Dielectric Withstand Voltage	UL Voltage Rating
2,000 V RMS	300 V RMS

#### Temperature Range

Operating Temp Range:	-40°C To +105°C
-----------------------	-----------------

#### Mechanical Characteristics

Bulk Cable Weight:	65 lbs/1000ft
--------------------	---------------

## Standards

UL Rating:	105°C, 300 V RMS, VW-1
UL AWM Style:	2651
CSA Rating:	105°C, 300 V RMS, FT1
CSA AWM Specification:	I A 105°C 300V FT1

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-07-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Indoor:	Yes
-----------------------	-----

## Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color
9L28050 008H100	Gray

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.