


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	51-00026.M	Connector, PPL7, 7C, 0° socket, 7x38 mm, chrome, solder, Ø2.5-5.2 mm wire, molding style	1	
2	30-00672	Wire, 6C BC, 28 AWG, UL20280, 300V, 80C, 4.7 mm, braided shield, FT2, TPU	1	
3	24-00206	Overmold, PPL7 strian relief, 10x24 mm	1	TPU
4	Heat shrink	Black	1	covers jacket end
5	Heat shrink	Black	1	covers drain



Wiring Diagram	
50-00026.M	wire color
1	Red
2	White
3	Black
4	Yellow
5	Blue
6	Green
7	Shield/ Drain

Revision: A	Date: 3/27/2018	Description: Initial release	Prepared:	Notes: RoHS and REACH compliant Function test: no open, no short circuit, no intermittent	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
			Verified:		
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 7C PPL7 socket 51-00026.M, to stripped tinned, 28 AWG, UL20280 30-00672	Size: A Part number: 10-02474
					Scale: 1:1  Sheet 1 of 1

5

4

3

2

1