



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Olive drab Cadmium
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 30.16 g ± 10%

| Connector dimension | |
|---------------------|-----------------|
| Dim | Nominal |
| A | 41.3±0.3 |
| B | 26.97+0.1/-0.15 |
| R | 32.5Max |
| S | 38.1±0.4 |
| W | 2.2+0.9/-0.1 |
| VV THREAD | M22x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D715W19PA


| | | | |
|--------------|------------|--------------------------|-------------------------|
| A | 08-11-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |

| | | | |
|--------------|--------------------------------|--|--|
| TITLE | Aluminium Receptacle 8D series | | |
|--------------|--------------------------------|--|--|

| | | | |
|-------|--|----------------------------|-----------------|
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |

| | | |
|----------------|------------------------|---|
| SOURIAU | WWW.SOURIAU.COM | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
|----------------|------------------------|---|

| | | | |
|-----------|------------------------------------|--|------------|
| FORMAT | SOURIAU DRG N° 8D715W19PA-C | | SHEET |
| A3 | | | 1/2 |



Contact Layout



| Contacts (Insert arrangement 15-19) | | | | | |
|--|-------------|-------------|---------------------|-------------|-------------|
| Contact position ID | Location | | Contact position ID | Location | |
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +000 (0.00) | +225 (5.72) | L | -195 (4.95) | +113 (2.87) |
| B | +130 (3.30) | +225 (5.72) | M | -130 (3.30) | +225 (5.72) |
| C | -195 (4.95) | +113 (2.87) | N | -005 (1.05) | +113 (2.87) |
| D | +260 (6.60) | +000 (0.00) | P | +065 (1.65) | +113 (2.87) |
| E | +195 (4.95) | -113 (2.87) | R | +130 (3.30) | +000 (0.00) |
| F | +130 (3.30) | -225 (5.72) | S | +065 (1.65) | -113 (2.87) |
| G | +000 (0.00) | -225 (5.72) | T | -065 (1.65) | -113 (2.87) |
| H | -130 (3.30) | -225 (5.72) | U | -130 (3.30) | +000 (0.00) |
| J | -195 (4.95) | -113 (2.87) | V | +000 (0.00) | +000 (0.00) |
| K | -260 (6.60) | +000 (0.00) | | | |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 15 | -19 | 19 | 20 | I | All | MS20052-19 |

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



Max. thickness panel for receptacle: Type 7: 3.2 mm

| Dim | Nominal |
|-----|---------------|
| B | 27.56+0/-0.25 |
| ØC | 28.83+0.25/-0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D715W19PA

| | | | |
|----------------|------------------------------------|----------------------------|---|
| A | 08-11-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Aluminium Receptacle 8D series | | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D715W19PA-C | | SHEET 2/2 |