



- Notes
- 1 The recommended tightening torque for the Ref No.5 is 5 N·m.
  - 2 This product has floating range of ±2mm from the center of the connector.
  - 3 There are some cases that plating color of Ref No.3 may change from silver to blackish brown due to chemical reaction by sulfre in the atmosphere.
  - 4 Busbar and copper bar shall be either silver plating.
  - 5 The recommended distance between installation site and tip of busbar shall be 17.85<sup>+0</sup> mm.

2	Stainless Steel		5	Steel	Nickel Plating : 2μm min
1	PBT	Black. UL94V-0	4	PBT	Black. UL94V-0
			3	Copper Alloy	Silver Plating : 2μm min
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS	mm	SCALE	1 : 1	COUNT	1
		DESCRIPTION OF REVISIONS		DESIGNED	MO. SHIMUYAMA
		DIS-E-0000752		CHECKED	NM. NISHIMATSU
				DATE	16.11.15
APPROVED : RI. TAKAYASU 15.12.16			DRAWING NO. EDC-128869-00-00		
CHECKED : NM. NISHIMATSU 15.12.15			PART NO. PS4-3.175T		
DESIGNED : MO. SHIMUYAMA 15.12.15			CODE NO. CL236-1012-0-00		
DRAWN : MO. SHIMUYAMA 15.12.15					