

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35°C TO + 85°C (NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO + 60°C
	VOLTAGE	50V AC	APPLICABLE CONNECTOR	DF21-30S-0.6V(56)
	CURRENT	AWG40 : 0.3A AWG36 : 0.5A	APPLICABLE CONTACT	THIN COAXIAL CABLE

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

--	--	--	--	--

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE

REMARKS NOTE 1:INCLUDING THE TEMPERATURE RISING BY CURRENT. Unless otherwise specifid , refer to JIS C 5402.	APPROVED	TY. OMA	07. 04. 24
	CHECKED	HK. UMEHARA	07. 04. 24
	DESIGNED	TS. FUKUSHIMA	07. 04. 19
	DRAWN	AK. MIURA	07. 04. 19

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-163696-02
--	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DF21-30P-0.6SD-GND(05)
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL687-2502-1-05
			1/1