



MATERIAL: COPPER
 .031" NOM. THICKNESS
 FINISH: ELECTRO-TIN PLATING

MWID= MAX. WIRE INSULATION DIA.
 PART NUMBERS ARE FOR LOOSE PIECE TO ORDER PARTS ON TAPE ADD A "T" TO END OF PART NUMBER

| MATERIAL NO. | ENGR NO. | WIRE RANGE AWG | DIAMETER "D" | MAX. "L" | ±.01 "B" | MWID | MIN. I.D. | | | INSULATION |
|--------------|----------|----------------|--------------|----------|----------|------|-----------|--|--|------------|
| 190340002 | A-259X | 22-18 | .180 | .950 | .450 | .145 | .056 | | | PVC |
| 190340005 | A-269X | 22-18 | .156 | .890 | .450 | .145 | .056 | | | PVC |
| 190340007 | B-279X | 16-14 | .180 | .950 | .450 | .175 | .084 | | | PVC |
| 190340009 | B-289X | 16-14 | .156 | .890 | .450 | .175 | .084 | | | PVC |
| | | | | | | | | | | |

REMOVED TAPE PARTS

| | |
|---------------|------------|
| EC NO: | 2005/04/27 |
| DRWN:LSHADECK | 2005/05/04 |
| CHKDR:DEROSS | 2005/05/04 |
| APPR:RDEROSS | 2005/05/04 |

| | |
|-----------------|-------------|
| QUALITY SYMBOLS | DESCRIPTION |
| ▽=0 | |
| ▽=0 | |

| | |
|---------------------------------------|-------------------------------|
| GENERAL TOLERANCES (UNLESS SPECIFIED) | |
| | mm INCH |
| 4 PLACES | ± --- ± --- |
| 3 PLACES | ± --- ± --- |
| 2 PLACES | ± --- ± --- |
| 1 PLACE | ± --- ± --- |
| ANGULAR | ± ---° |
| DRAFT WHERE APPLICABLE | MUST REMAIN WITHIN DIMENSIONS |

| | |
|------------------------|----------|
| DIMENSION STYLE | IN/MM |
| SCALE | 5:1 |
| DESIGN UNITS | INCH |
| THIRD ANGLE PROJECTION | |
| DRAWN BY | DATE |
| EMF | 07/30/93 |
| CHECKED BY | DATE |
| JM | 07/30/93 |
| APPROVED BY | DATE |
| FP | 07/30/93 |

| | |
|---|----------------------------------|
| TITLE | INSULKRIMP MALE BULLET SNAP PLUG |
| MATERIAL NO. | SEE TABLE |
| DOCUMENT NO. | SD-19034-004 |
| SHEET NO. | 1 OF 1 |
| THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | |