



Material:

- 1.Cable: #28,UL2919, 3COAXIAL+7C+1+AL/MY+Braid,
(Beige PVC Jacket) O.D:8.5
- 2.Connector: HD15M, 9th Empty, Black
- 3.Thumbscrew:#4-40UNC, E32
- 4.Ferrite Core Size:RH 16*28*9
- 5.Black Heat Shrink:∅1.5x15:6PCS ∅3x8:6PCS
- 6.Copper Size:30X50

Note:

- 1.Total Length:5000±50mm
- 2.Color: Beige
- 3.Molded Type

Configuration:

HD15M		HD15M
1	Red(Coax)	1
6	Red(Ground)	6
2	Green(Coax)	2
7	Green(Ground)	7
3	Blue(Coax)	3
8	Blue(Ground)	8
4	Brown	4
5	Black	5
13	Green	13
14	Red	14
10	Orange	10
11	White	11
12	Yellow	12
Shield	(Braid)	Shield

Description	
Name	AK3770XF-R
HD15 Male-HD15 Male W/Copper Foil+ 2Ferrite Core	



THIS DRAWING IS UNPUBLISHED

© Copyright 2005 by Assmann Electronic Components All International Rights Reserved

This drawing is a controlled document for Assmann Electronics, Inc. It is subject to change and the controlling engineering organization should be contacted for the latest revision.