

Cable tie - PKB 370X4,8 BK - 1005567

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Cable tie, resistant to UV rays, dimensions: L x W, 370 x 4.8 mm, color: black



Product Features

- The plastic cable binders are ideal for use with WMTB, KMK 2, and KMK 4 cable markers from Phoenix Contact
- With the UNIFOX-CT ... cable binder tool, the cable binders can be easily tightened and cut off in one step
- UV stabilized (black), for use in outdoor systems
- For bundling control lines and cables
- Transparent, for standard applications
- The cable binders can be used indoors and outdoors even under unfavorable industrial conditions

Key commercial data

Packing unit	1 PCE
Minimum order quantity	1000 PCE
Weight per Piece (excluding packing)	2.56 GRM
Custom tariff number	39269097
Country of origin	Singapore

Technical data

Dimensions

Length (b)	370 mm
Width (a)	4.8 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

General

Color	black
Inflammability class according to UL 94	V2
Material	PA

Cable tie - PKB 370X4,8 BK - 1005567

Classifications

eCl@ss

eCl@ss 4.0	27140702
eCl@ss 4.1	27140702
eCl@ss 5.0	27140702
eCl@ss 5.1	27140702
eCl@ss 6.0	27140702
eCl@ss 7.0	27140702
eCl@ss 8.0	27140702

ETIM

ETIM 2.0	EC000046
ETIM 3.0	EC000046
ETIM 4.0	EC000046
ETIM 5.0	EC000046

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703