



P/N Tin Lead version	P/N Tin version
5043EF48--Y2--G	5043EF48--Y2-GLF

NOTE RoHS INFORMATIONS

- The "LF" products meet European Union Directives and other country regulations as described in GS-22-008
- The housing will withstand exposure to 260°C peak temperature for 3.5 seconds in a wave solder application with a 1.6 mm minimum thick circuit board. See application notes/procedures if they are available.
- Packaging spec: see GS-14-920

www.fciconnect.com		surface - ✓	tolerance std	projection	mm
		ISO 1302	ISO 406 ISO 1101		
		TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	D LEGRAND	04.01.02	ANGULAR	LINEAR	size A3
Eng	F. TISSERAND	04.01.02	0.X	±0.3	Scale 2:1
Chr	JF NOTTEAU	04.01.02	0.XX	±0.1	
Appr	F. TI	04.01.02	0.XXX	±0.05	ECN LS07-0057
		Product family	- Spec ref		
	title	ASSY 5043		dwg no	VJW53613
	5043 EF 48..Y2.G	VXX27771			
	catalog no	CUSTOMER		sheet 1 of 1	

lfr	ecn no	dr	date
A	F03002	DLE	04.01.02
B	LS07-0057	HLE	07/02/27
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



Copyright FCI.