

Slave protocol chip - IBS SUP14 TQFP - 2988117


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Slave protocol chip, for INTERBUS



RoHS

Key Commercial Data

Packing unit	160 STK
Minimum order quantity	160 STK
GTIN	 4 046356 341752
GTIN	4046356341752

Technical data

Dimensions

Width	10 mm
Height	1 mm
Depth	10 mm
Length	10 mm

Ambient conditions

Ambient temperature (storage/transport)	-65 °C ... 150 °C (at max. 60 %)
Ambient temperature (operation)	-40 °C ... 85 °C (at max. 75% humidity during operation)

Module

IC power supply voltage	3.3 V DC ±10 % (DC)
Typical current consumption	20 mA
Connection method	Remote bus, local bus or installation remote bus
Interface	INTERBUS
Internal data length	64 bytes IN/64 bytes OUT
User interface	MFP interface, digital I/O (16 IN/16 OUT, 32 IN, 32 OUT), parallel and serial port for microprocessors

General

Slave protocol chip - IBS SUPI 4 TQFP - 2988117

Technical data

General

Type	TQFP 64
------	---------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>