

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2009

© COPYRIGHT 2009

BY -

ALL RIGHTS RESERVED.

LOC
EDIST
B

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
C		ECR-12-010466	08JUN2012	KR	JC

NOTES:

- 1 RATED POWER @ 70°C: 40W
- 2 RESISTANCE: 160 Ohms
- 3 TOLERANCE: 5%
- 4 TEMP. COEFFICIENT: ±300ppm/°C
- 5 OPERATING TEMP. RANGE: -55 to +250 °C
- 6 INSULATION RESISTANCE: 1000MOhms
- 7 FOR FURTHER INFORMATION SEE DATA SHEET FOR SQ SERIES-HIGH POWER RESISTOR (1773285)

RoHS Compliant

SCALE 1:1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN SUBHASH.M 24-MAR-09

CHK C.BOLLE 24-MAR-09

APVD J.CATCHPOLE 24-MAR-09

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

STE

TE Connectivity

NAME
HIGH POWER RESISTOR
SQH40 160R 5% 6.35mm FASTON

RESTRICTED TO

SIZE A3 CAGE CODE 00779 DRAWING NO. C-1879556

SCALE 2:1 SHEET 1 OF 1 REV C

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±0.5
1 PLC	±0.2
2 PLC	±0.1
3 PLC	±
4 PLC	±
ANGLES	±0.5°
FINISH	-

MATERIAL

-

FINISH

-

ITEM	TE PART NO	MEC PART NO	DESCRIPTION
1	0-1879556-1	SQHW40160RJ6	SQH40 160R 5% 6.35mm FASTON

1470-19 (3/11)

Pro/ENGINEER DRAWING