

Panel feed-through - Q 0,75/4FL/11-M20KU-ESA - 1640650

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



QUICKON panel feed-through, for external wall mounting with manual solder/slip-on connection, 2.8 x 0.8 mm. 4-pos.



Key commercial data

| | |
|--------------------------------------|-----------|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| Weight per Piece (excluding packing) | 20.45 GRM |
| Custom tariff number | 85369010 |
| Country of origin | Poland |

Technical data

General

| | |
|--|---|
| Connection | If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load. |
| Color | green |
| Connection method | QUICKON connection Manual solder/slip on connection |
| Number of positions | 4 |
| Wrench size, union nut | 22 mm |
| Tightening torque, union nut | 2.5 Nm |
| Wrench size, contact carrier | 22 mm |
| Tightening torque contact carrier | 3.75 Nm |
| Tightening torque, counter nut | 3.75 Nm |
| Number of connections | 4 |
| Conductor cross section stranded min. | 0.34 mm ² |
| Conductor cross section stranded max. | 0.75 mm ² |
| Conductor cross section AWG/kcmil min. | 22 |

Panel feed-through - Q 0,75/4FL/11-M20KU-ESA - 1640650

Technical data

General

| | |
|---------------------------------------|----|
| Conductor cross section AWG/kcmil max | 18 |
|---------------------------------------|----|

Conductor

| | |
|---|--|
| Structure of individual litz in acc. with VDE 0295 / smallest wire diameter | Class 2-6 // 0.34 mm ² : 0.1 mm; 0.5 - 0.75 mm ² : 0.15 mm |
| Wire insulation material | PVC/PE |
| Wire diameter including insulation | 2.5 mm |

Ambient conditions

| | |
|---------------------------------|---|
| Degree of protection | IP65 |
| | IP67 |
| Ambient temperature (operation) | -25 °C ... 80 °C (Specifications of the cable manufacturer must be observed.) |
| | -25 °C ... 50 °C (when the conductor is connected. Specifications of the cable manufacturer must also be observed.) |

Electrical characteristics

| | |
|-----------------------------------|------------------------|
| Nominal current I _N | 9 A |
| Rated voltage (III/3) | 160 V |
| Note on the rated voltage (III/3) | with insulating sleeve |
| Rated voltage (III/2) | 160 V |
| Note on the rated voltage (III/2) | with insulating sleeve |
| Rated voltage (II/2) | 320 V |
| Note on the rated voltage (II/2) | with insulating sleeve |

Mechanical characteristics

| | |
|------------------------|--|
| QUICKON connectability | 10 (if the conductor is connected more than once, seal and cap may need to be replaced.) |
| PC QUICKON thread type | M20 x 1,5 |
| Impact category | 3 |

Material data

| | |
|---|----------------------------------|
| Contact material | Cu alloy |
| Contact surface material | Pre-nickel plated and tin-plated |
| Contact carrier material | PA |
| Inflammability class according to UL 94 | V0 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140815 |
| eCl@ss 4.1 | 27140815 |

Panel feed-through - Q 0,75/4FL/11-M20KU-ESA - 1640650

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.0 | 27143423 |
| eCl@ss 5.1 | 27143423 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 7.0 | 27449001 |
| eCl@ss 8.0 | 27449001 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001297 |
| ETIM 3.0 | EC000516 |
| ETIM 4.0 | EC000516 |
| ETIM 5.0 | EC000516 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211923 |
| UNSPSC 7.0901 | 39121522 |
| UNSPSC 11 | 39121522 |
| UNSPSC 12.01 | 39121522 |
| UNSPSC 13.2 | 39121522 |

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / GOST / GOST / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

Panel feed-through - Q 0,75/4FL/11-M20KU-ESA - 1640650

Approvals

| | |
|--------------------|-------|
| UL Recognized | |
| | |
| Nominal current IN | 9 A |
| Nominal voltage UN | 250 V |

| | |
|--------------------|-------|
| cUL Recognized | |
| | |
| Nominal current IN | 6 A |
| Nominal voltage UN | 250 V |

| | |
|------|--|
| GOST | |
|------|--|

| | |
|------|--|
| GOST | |
|------|--|

| | |
|------------------|--|
| cULus Recognized | |
|------------------|--|

Accessories

Accessories

Insulating sleeve

Insulating sleeve - PT/FS 2,8 - 1406700



Insulating sleeve, as touch protection, slide onto the conductor before for 2.8 slip-on sleeves

Mounting material

Panel feed-through - Q 0,75/4FL/11-M20KU-ESA - 1640650

Accessories

Nut - Q-MU M20 - 1640702



Nut (plastic) to lock the contact carrier from the inside of the device

Mounting material - Q SET- 9 DI/KR - 1640362



Seal/Collar replacement set Pg9

Protective cap

Filler plugs - Q-PROT 9/11 - 1670235



Closing cap for Pg9/Pg11 to close unoccupied connections

Drawings

Dimensioned drawing

