



CONTACT CONFIGURATION

SWITCH FUNCTION	POS. 1	POS. 2	POS. 3
2-3,5-6	DN	DN	DN
8-9,11-12	DN	DN	DN

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4 X:XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 5A@ 120VAC OR 28VDC 2A@ 250VAC
5. ELECTRICAL LIFE: 40,000 CYCLES AT FULL LOAD
6. INSULATION RESISTANCE: 1000M OHMS MIN.
7. DIELECTRIC STRENGTH: 1000V RMS
8. OPERATING TEMP: -30C TO + 85C



100 4P1 T6 B11 M1 Q E

B	16565	11.43 TO 12.30 CORRECTION	10/23/06	TN
A	12901	RELEASED FOR PRODUCTION	12901	RC
REV.	ECN No.	DESCRIPTION	DATE	CHKD

SCALE	DATE	DR	DWG	REV
NONE	3/12/03	RC	T141009	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED