

Coupler connector - CA-07S1N8A9008 - 1620038

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling connector, straight, shielded: yes, SPEEDCON locking, M23, Number of positions: 7, Type of contact: Socket, Crimp connection, Cable diameter: 10 mm ... 14.5 mm

The figure shows the 6-pos. product version

Product Features

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Crimping connection: vibration- and temperature-resistant assembly



Key Commercial Data

| | |
|----------------------|----------|
| Packing unit | 1 pc |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

Temperature range

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

Data of the insulating body

| | |
|---|--|
| Note | Order information Order crimp contacts Ø 2 mm separately |
| Coding | N |
| Insulator material | PA 66 |
| Contact connection method | Crimp connection |
| Type of contacts | Socket |
| Number of positions | 7 |
| Contact diameter of power contacts | 2 mm |
| Nominal current per power contact at 25°C | 20 A |

Coupler connector - CA-07S1N8A9008 - 1620038

Technical data

Data of the insulating body

| | |
|--------------------------------|-------|
| Nominal voltage, power contact | 300 V |
| Overvoltage category | II |
| Degree of pollution | 3 |

Housing data

| | |
|--|--|
| Housing material | Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn) |
| Type of locking | SPEEDCON locking |
| Degree of protection (when plugged in) | IP67 |
| Thread type | M23 |

Cable seal data

| | |
|---------------------|---------|
| Min. cable diameter | 10 mm |
| Max. cable diameter | 14.5 mm |
| Sealing material | NBR |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 272607xx |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260702 |
| eCl@ss 7.0 | 27440102 |
| eCl@ss 8.0 | 27440102 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002635 |
| ETIM 5.0 | EC002635 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201404 |
| UNSPSC 13.2 | 43201404 |

Coupler connector - CA-07S1N8A9008 - 1620038

Approvals

Approvals


Approvals

UL Recognized / cUL Recognized / EAC

Ex Approvals

Approvals submitted

Approval details


UL Recognized 

cUL Recognized 

EAC

Drawings

Schematic diagram



Dimensional drawing

