

## Specification Sheet

Part Number: 596-00207



Solar Marker, Reflective, Non-Adhesive, WARNING: PV POWER SOURCE, 4" x 2", VL, Red, 25/pkg

Article Number	596-00207
Type	PVPSSNAP4
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none"><li>• Pre-Printed Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life.</li><li>• Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.</li><li>• Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.</li><li>• The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.</li></ul>
Quantity Per	pack

**Product Description**

These HellermannTyton photovoltaic caution and power source markers are designed to meet the requirements of the National Electrical Code (NEC) International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Coiled markers are pre-printed, non-adhesive and made of a UV stable vinyl. Markers can be opened and snapped over cables for long-term, reflective, permanent identification. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed. Vinyl markers fit all standard PV cables or electrical metallic tubing (EMT) conduits.

**Short Description**

Solar Marker, Reflective, Non-Adhesive, WARNING: PV POWER SOURCE, 4" x 2", VL, Red, 25/pkg

**Global Part Name**

PVPSSNAP4-V-RD

**Technical Description**

Pre-Printed Solar Marker, Reflective, Non-Adhesive, Coiled, "WARNING: PHOTOVOLTAIC POWER SOURCE", 4" X 2", Red

**Length L (Imperial)**

2.0

**Length L (Metric)**

50.80

**Width W (Imperial)**

4.0

**Width W (Metric)**

101.6

**Material**

Vinyl

**Material Shortcut**

V

**Halogen free**

Yes

**Operating Temperature (Metric)**

-18°F to +200°F (-29°C to +93°C)

<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	IFC 2012 NEC2011
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3919905060
<b>Content Unit(BMEcat)</b>	pack