

## Specification Sheet

Part Number: SAM83HIRHSH1



Axial Oval Mount, Bolt Hole Diameter 0.31", PA66HIRHS, Gray, 500/pkg

<b>Article Number</b>	151-29600
<b>Type</b>	SAM83
<b>Color</b>	Gray (GY)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Positions bundles off cross members and frame rails to prevent abrasion and chafing.</li><li>• Metal insert bushing accommodates high-torque installation.</li><li>• Made with high-impact, heat stabilized, and UV material ideal for trucking and heavy equipment environments.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton's axial oval mount stands off bundles from frame rails and cross members to prevent them from rubbing and chafing. The axial oval mount accommodates cable ties up to 0.5" wide. The hole on the mount was designed to fit a 5/16" bolt.
<b>Short Description</b>	Axial Oval Mount, Bolt Hole Diameter 0.31", PA66HIRHS, Gray, 500/pkg

Global Part Name

SAM83-PA66HIRHSUV-GY

Length L (Imperial)

1.40

Length L (Metric)

34.0

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

1.0

Width W (Metric)

26.0

Cable Ties

T50 - T250

Height H (Imperial)

1.40

Height H (Metric)

35.0

Cable Tie Width Max (Imperial)

0.5

Cable Tie Width Max (Metric)

12.7

Mounting Hole Diameter D (Imperial)

0.31

Mounting Hole Diameter D (Metric)

8.0 mm

Mounting Hole Diameter D Min (Imperial)

0.31

Mounting Hole Diameter D Max (Imperial)

0.31

Mounting Hole Diameter D Max (Metric)

8.0

Stud Diameter (Metric)

8.0 mm

<b>Stud Diameter (Imperial)</b>	0.3125
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.