


| APPLICABLE STANDARD  |  |   |                           |   |
|--|--|---|---------------------------|---|
| RATING   | OPERATING TEMPERATURE RANGE  | -65°C TO +125°C   | STORAGE TEMPERATURE RANGE | -40°C TO +85°C  |
|  | POWER  | 2(AT 25°C) W CW<br>1(AT 65°C) W CW  | CHARACTERISTIC IMPEDANCE  | 50Ω (DC TO 8 GHz)   |
|  | OPERATING RELATIVE HUMIDITY  | 95% MAX   | USED CONNECTOR            | HRM-P , HRM-J   |
| <b>SPECIFICATIONS</b>  |  |   |                           |   |
| ITEM   | TEST METHOD  | REQUIREMENTS  | QT                        | AT  |
| <b>CONSTRUCTION</b>  |  |   |                           |   |
| GENERAL EXAMINATION  | VISUALLY AND BY MEASURING INSTRUMENT.  | ACCORDING TO DRAWING.   | X                         | X   |
| MARKING  | CONFIRMED VISUALLY.  |   | X                         | X   |
| <b>ELECTRIC CHARACTERISTICS</b>                                |  |   |                           |   |
| V.S.W.R.   | MUST BE UNDER THE STD.VALUE AT FREQUENCY DC TO 4.0 GHz   | MAXIMUM OF 1.15   | X                         | X   |
|  | MUST BE UNDER THE STD.VALUE AT FREQUENCY 4.0 TO 8.0 GHz  | MAXIMUM OF 1.20   |                           |   |
| ATTENUATION  | MUST BE UNDER THE STD.VALUE AT FREQUENCY DC TO 8.0 GHz   | 28.8 TO 31.2 dB.  | X                         | X   |
| ISOLATION  | MUST BE UNDER THE STD.VALUE AT FREQUENCY TO GHz  | MINIMUM OF dB.  | -                         | -   |
| INSULATION RESISTANCE  | MUST BE OVER STANDARD VALUE AT DC V.   | MINIMUM OF MΩ   | -                         | -   |
| VOLTAGE PROOF  | V AC FOR 1 min.CURRENT LEAKAGE 2mA MAX.  | NO FLASHOVER OR BREAKDOWN.  | -                         | -   |
| RESISTANCE VALUE   | MEASURE THE RESISTANCE VALUE AT DC1V.  | Ω ± %   | -                         | -   |
| <b>MECHANICAL CHARACTERISTICS</b>                              |  |   |                           |   |
| CABLE CLAMP ROBUSTNESS (AGAINST CABLE PULL)                    | APPLYING A PULL FORCE THE CABLE AXIALLY AT N MAX.  | ①NO WITHDRAWAL AND BREAKAGE OF CABLE.<br>②NO BREAKAGE OF CLAMP.                         | -                         | -   |
| VIBRATION  | FREQUENCY 10 TO 2000 Hz, SINGLE AMPLITUDE 0.75 mm, 98 m/s <sup>2</sup> AT 4 HOURS, FOR 3 DIRECTIONS.             | NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.  | X                         | -   |
| SHOCK  | 490 m/s <sup>2</sup> AT 10 TIMES FOR 3 DIRECTIONS.   | NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.  | X                         | -   |
| <b>ENVIRONMENTAL CHARACTERISTICS</b>                           |  |   |                           |   |
| DAMP HEAT (STEADY STATE)                                       | EXPOSE TO °C, ~ %, h. THEN LEAVE IT FOR ONE HOUR OR TWO IN THE AMBIENT TEMPERATURE AND HUMIDITY.                 | ①ELECTRICAL CHARACTERISTIC SHALL BE MET.<br>②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS. | -                         | -   |
| RAPID CHANGE OF TEMPERATURE                                    | TEMPERATURE -65 → - → +125 → - °C<br>TIME 30 → - → 30 → - min<br>TEST 5 CYCLES AND LEAVE IT FOR ONE HOUR OR TWO. | NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.  | X                         | -   |
| SALT SPRAY (CORROSION)   | EXPOSE TO 5 % SALT WATER SPRAY FOR 48 HOURS.   | NO CORROSION WHICH AFFECTS THE OPERATION OF COMPONENT.                                  | X                         | -   |
|  |  |   |                           |   |
| COUNT  | DESCRIPTION OF REVISIONS   | DESIGNED  | CHECKED                   | DATE  |
| 0  |  |   |                           |   |
| REMARK   |  | APPROVED  | KY. SHIMIZU               | 15. 10. 28  |
| RoHS COMPLIANT   |  | CHECKED   | TO. KATAYAMA              | 15. 10. 28  |
|  |  | DESIGNED  | YI. FUNADA                | 15. 10. 28  |
| Unless otherwise specified, refer to IEC 60512.                |  | DRAWN   | YI. FUNADA                | 15. 10. 28  |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test |  | DRAWING NO.   | ELC4-181142-00            |   |
| <b>HRS</b>   | SPECIFICATION SHEET  | PART NO.  | AT-130V                   |   |
|  | HIROSE ELECTRIC CO., LTD.  | CODE NO.  | CL354-0279-6-00           |  1/1 |

May.1.2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.