

**Part Number: 9875**

Audio, Control & Instrument, #20-9pr, PO, Individ. Foil, PVC Jkt, CM



## Product Description

Audio, Control & Instrument Cable, 20 AWG stranded (7x28) tinned copper conductors, polypropylene insulation, twisted pairs, individually shielded with Beldfoil® (100% coverage), 22 AWG stranded tinned copper drain wire, overall PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors	No. of Pairs
20	7x28	TC - Tinned Copper	18	9

Conductor Count:	18
Conductor Size:	20 AWG

#### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.015 in

#### Color Chart

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown
7	Black & Orange
8	Red & White
9	Red & Green

#### Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil® (Z-Fold®)	100 %	TC - Tinned Copper	22	19x34 mm

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.555 in	0.052 in

### Electrical Characteristics

#### Conductor DCR

Individual Pair Nominal Shield DCR	Nominal Conductor DCR
11.3 Ohm/1000ft	10.5 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
30 pF/ft	55 pF/ft

Shielding:	Individually Foiled + No Overall
------------	----------------------------------

## Inductance

### Nominal Inductance

0.18 µH/ft

## Impedance

### Nominal Characteristic Impedance

50 Ohm

## Delay

### Max. Delay Skew | Nominal Velocity of Propagation (VP) [%]

66 ns/100m | 66 %

## Current

### Max. Recommended Current [A]

2 Amps per conductor @ 25°C A

## Voltage

### UL Description | UL Voltage Rating

UL AWM Style 2919 | 30 V RMS

CM | 300 V RMS

## Temperature Range

UL Temp Rating: 80°C (UL AWM Style 2919)

Operating Temp Range: -20°C To +80°C

## Mechanical Characteristics

Bulk Cable Weight: 157 lbs/1000ft

Max Recommended Pulling Tension: 320 lbs

Min Bend Radius/Minor Axis: 5.75 in

## Standards

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CM

UL AWM Style: 2919 (30 V 80°C)

## Applicable Environmental and Other Programs

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2004-01-01

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability: UL1685 UL Loading

UL voltage rating: 30 V RMS

## Plenum/Non-Plenum

Plenum (Y/N): No

## Part Number

### Variants

Item #	Color	Footnote
9875 060100	Chrome	C
9875 0601000	Chrome	C
9875 060500	Chrome	C
9875 0605000	Chrome	

Footnote: C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.