

Laird TechnologiesWeb site: www.LairdTech.com

All Categories > Antennas & Reception Solutions > In-Building, CPE, Access Point, and Mobile Client Antennas > CPE Antennas (WiMAX, 3G/4G, LTE, Cellular, BWA) > Cellular (CELL) Antennas > Laird Technologies Dual Feed, Linear & Circular Panel Antennas (CELL) > 800/900 MHz. Omnidirectional Antennas for Data Communications > DirectLink™ Series Antennas > Item # S1856MPC10NF

Item # S1856MPC10NF, DirectLink™ Series Antennas[larger image](#)**Campus & in-building directional antennas**[Stock Locator](#)

DirectLink is a series of wall and mast mount directional antennas that has been designed to meet the most demanding needs of the contemporary wireless environment. DirectLink's attractive, UV resistant housings and mounts allow the antennas to be mounted anywhere in the campus or in-building environment. The antennas offer very precise and controllable pattern characteristics in frequencies starting with the 1710

MHz DCS band and continuing through the 5.725 GHz ISM band. All popular contemporary wireless system applications are covered with gain characteristics varying with frequency.

All antennas in the series may be wall or mast mounted and all are available with a variety of flush and articulating mounts. Flush mounts allow the antenna to hug the wall for minimal visual impact. There are two available articulating mounts that allow the pattern to be directed while still maintaining minimal visual impact.

Standard antennas come with either TNC, SMA or N female connectors and an integrated coaxial pigtail. Other connector and pigtail combinations are available upon request.

Specifications

Band	DCS ISM
Frequency	1850 to 1990 MHz
Gain	6 dBic
3dB Beamwidth, E Plane	70 °
3dB Beamwidth, H Plane	70 °
VSWR	1.5:1
Front to Back Ratio	20 dB
Connector	N (Female)
Articulating Version	Yes
Power	75 watts
Power at 5 GHz	25 watts

Polarization	Linear
Standard Wall Mount Dimension	5.70 x 3.81 x 1.50 in 14.48 x 9.68 x 3.80 cm
Articulating Wall Mount Dimension	5.80 x 3.81 x 2.26 in 14.73 x 9.68 x 5.74 cm
Weight (Standard Wall Mount)	5 oz 0.14 kg
Weight (Articulating Wall Mount)	8 oz 0.23 kg
Mounting Style	Standard units for wall mounting. Mast mount bracket kits available. Custom mount configurations for volume users.
Cable	Low loss pigtail provided

[Print](#) [Back](#)