

1

2

3

4

5

CHARACTERISTICS:

MATERIAL:  
COLOR: BLACK  
STYLE: UL1061


ENVIRONMENTAL  
OPERATING TEMPERATURE: -20°C UP TO 80°C  
COMPLIANCE: LEAD FREE AND ROHS

WIRE DIMENSION:  
AWG: 30

PACKAGING:  
10 PCS/BAG

3 mm Pre-stripped

Wire end A



Wire end B

Wire Length 150mm

Wire end A	66500113722
Wire end B	Pre-stripped

RoHS Compliant

G			
F			
E			
D			
C			
B			
A	12-SEP-13	PDF	QL
REV	DATE	FILE	BY

PROJECTION:



GENERAL TOLERANCE

.X = +/- 0.2  
.XX = +/- 0.15



APPROVAL: BBu

UNIT: MM

SCALE:

SHEET: 1/2

DRAW: QL

DESCRIPTION: WR-WTB 1.00 MM PRE-CRIMPED CABLE

WERI PART NO: 665 100 130 115

SIZE

**A4**

1

2

3

4

5

## Cautions and Warnings:

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

A

B

C

RoHS Compliant

G				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15		
F							
E							
D							
C				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE <b>A4</b>
B					SCALE:		
A	10-SEP-14	PDF	QL		SHEET: 2/2	WERI PART NO: DISCLAIMER	
REV	DATE	FILE	BY		DRAW: QL		

D