



APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING & STORAGE HUMIDITY RANGE	85%MAX 	APPLICABLE CABLE	TINNED ANNEALED COPPER SIZE : AWG28 STRANDING : 7/0.127 INSULATION DIAMETER : $\phi 0.9 \pm 0.04$
	VOLTAGE	AC 125V 		
	CURRENT	0.5 A		


### SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----


#### CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X


#### ELECTRICAL CHARACTERISTICS


CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	50 mΩ MAX. (SIGNAL) 	X	X
INSULATION RESISTANCE	100 V DC.	1000 MΩ MIN.	X	—
VOLTAGE PROOF	250 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	X

#### MECHANICAL CHARACTERISTICS



INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE 25N MAX. WITHDRAWAL FORCE 2.6 N MIN.	X	—
MECHANICAL OPERATION	1000 TIMES INSERTIONS AND EXTRACTIONS.	1) CONTACT RESISTANCE 70 mΩ MAX.  2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES.	1) NO ELECTRICAL DISCONTINUITY OF 10 μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
SHOCK	490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	—

#### ENVIRONMENTAL CHARACTERISTICS



THERMAL SHOCK	TEMP -55 → +5 TO +35 → +85 → +5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.	1) CONTACT RESISTANCE: 70 mΩ MAX.  2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
HUMIDITY LIFE	TEMPERATURE 40 °C, HUMIDITY 90 TO 95 %, FOR 96 h	1) INSULATION RESISTANCE: 100 MΩ MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, FOR 48 h.	NO HEAVY CORROSION THAT LOSE FUNCTION.	X	—

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 1	DIS-E-003445	TF. HIGASHIYAMA	KN. ICHIKAWA	10.09.29

#### REMARK

 EXCLUDES CONDUCTOR RESISTANCE OF CABLE.  2 EXAMINATION IS HELD WITH "DH-17-CV * B", "DH30B-17S" AND "DH60-17P" OR "DH-17-CT * B", "DH30B-17S" AND "DH60A-17P *". Unless otherwise specified, refer to JIS C 5402 .	APPROVED	AO. SUZUKI	09.04.13
	CHECKED	MO. SHIMOYAMA	09.04.10
	DESIGNED	TS. ITO	09.04.10
	DRAWN	TS. ITO	09.04.10

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-126594-00
--	-------------	----------------

	SPECIFICATION SHEET	PART NO.	DH30B-17S	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0017-4-00	 1/1